


Synapse-Xbee Adapter Kit

Ever want to change the species of your RF modules? Upgrade your XBee-footprint devices to the more feature-rich Synapse series of 2.4GHz radios!



Build Time: 20mins
Skill Level: Beginner (2/5)

- Drop-in XBee replacement
- Second UART access

- Tx/Rx/GPIO indicators
- Open Source Hardware



 **SOLARBOTICS**® Ltd

www.solarbotics.com

1-866-276-2687

SKU: 39252

<http://www.solarbotics.com/products/39252/>

DocRev: August 29, 2011

Introduction:

The XBee series of 2.4GHz modules are very cool, but the Synapse series trumps them with a second UART, I2C, extra I/O, and even PWM. And they use embedded Python! This adapter board lets a **Synapse 802.15.4 RF Module** act as a drop-in replacement for a 10-pin XBee module application. The pin mapping is designed for best device-to-device matching with the exception of power, UART, reset, and the reserved pins.

There are 2 breakout headers on this board:

The 3-pin header **P1** includes breakout pins XB TX & XB RX, which are for the main UART communication lines that are used by both the XBee and Synapse Modules. These pins are attached to the following:

- **XB TX** (Data Out): Xbee Pin 2 (DOUT) pins to Synapse Pin 10 (GPIO8_TX_UART1)
 - **XB RX** (Data In): Xbee Pin 3 (DIN/!CONFIG) to Synapse Pin 9 (GPIO7_RX_UART1)
 - **GND:** Connection to the negative reference of power
- The 3-pin header **P2** includes breakout pins TX0 & RX0, which are for the other UART port that the Synapse Module has (UART0). These pins are attached to the following:
- **Tx0** (Data Out): Synapse Pin 6 (GPIO4_TX_UART0)
 - **Rx0** (Data In): Synapse Pin 5 (GPIO3_RX_UART0)
 - **GND:** Connection to the negative reference of power.

This design is release under the Open Source Hardware Definition v1.0

Disclaimer of Liability & other Legalese

Solarbotics Ltd.® is not responsible for any special, incidental, or consequential damages resulting from any breach of warranty, or under any legal theory, including lost profits, downtime, good-will, damage to or replacement of equipment or property, and any costs or recovering of any material or goods associated with the assembly or use of this product. Solarbotics reserves the right to make substitutions and changes to this product without prior notice. Yadda Yadda, blah, blah, blah. Sorry for the lawyerspeak.

"SOLARBOTICS" is a trademark of Solarbotics Ltd. Reg. CIPO / USPTO.

Parts & Materials List


6.8 μ F
Electrolytic
capacitor




5mm
Super
bright
LEDs




Adapter PCB



3-pin 0.1"
Male headers




10-pin
2mm
Male
headers



220 ohm resistors



12-pin 2mm
Female headers




Tools & Materials Needed:

- Soldering supplies
- Safety glasses
- Side cutters
- Masking tape (optional)

QTY	Part	Designators
3	5mm LED (1 each of red, green, orange)	GPIO1, GPIO3, GPIO4
3	220 Ohm resistor (red red brown)	R1, R2, R3
2	12-pin 2.0mm Spacing female header	
2	10-pin 2.0mm Spacing male header	
2	Synapse-Xbee Adapter PCB	
1	6.8uF 35V Electrolytic cap	C1
1	3-pin 0.1" Spacing male header	


Circuit Diagram



Construction


1. Pins / Headers: Take your Synapse-Xbee Adapter PCB and solder on the 10-pin male header pins on the side with the Solarbotics Logo.

If necessary, use some tape to hold the pins in place while you solder.



2. Resistors: Bend the 220 ohm resistor leads tight against the resistor body and install in the R1, R2, & R3 positions. Solder and trim!


Bend the resistor leads 90° to the body of the resistor. Try to keep them tight against the body.



Installed and soldered!

Construction

3. Capacitor: Bend the leads on the 6.8 μ F electrolytic capacitor to the *left* of the negative symbol on the cap. Install it flat, at 'C1', matching the orientation pictured on the board markings (also observing polarity) and solder it in place. It must lay flat to avoid the Synapse module to be installed above it.



4. LEDs: Time for Rx / Tx / GPIO LED indicators. We prefer to use Green for TX0, Red for RX0, and Orange for GPIO1. If your LEDs are clear, color-test them with a coincell battery, or take your chances! Just remember to match the shape, or put the shorter lead through the *square* pad. Install, solder and clip!

5. Communication Header: We broke out both the UART1 (XBee UART) and UART0 (Synapse Spare) to this pair of headers for easy comms hacking. Install the two 3-pin headers here, then solder, and trim! You're done!



Applications

If you already have Xbee hardware, like the Xbee Shield by Arduino, you can use your Arduino board to program the synapse module through the Xbee Shield (remove the Arduino IC, and set jumpers to USB).




You can use a Synapse module with the Lilypad as a longer range drop-in replacement for an Xbee. Use this application for e-textile projects where wireless controls/readings are needed, or you can use the Synapse module to control and communicate with other modules sewn onto other costumes and/or garments.



Here's a nifty trick:

You can always go the other way if you'd like to adapt an Xbee module to a board designed for Synapse modules. Just add a set of 12 male headers and 10-pin female headers (both 2mm spacing) to an unpopulated Synapse-Xbee Adapter PCB, and you can then use Xbee modules on Synapse boards.



Technical Support

Technical support is available if you are having problems - please contact us and provide as much detailed information as possible.

E-mail: support@solarbotics.com

Related Items

**Solarbotics Synapse-to-FTDI
Adapter** SKU# 39250



**Synapse Max Range Mesh
with RP-SMA Connector**
SKU# 51750



**Synapse Max Range Mesh
with RP-SMA Connector**
SKU# 51762



**Synapse Max Range Mesh
with Integrated Antenna**
SKU# 51752



Visit us online for more info and cool stuff:

www.solarbotics.com

Solarbotics Ltd.
3740D - 11A Street NE, Suite 101
Calgary, Alberta T2E 6M6
Canada



Toll Free: 1-866-276-2687
International: +1 (403) 232-6268



Fax: +1 (403) 226-3741



Made in Canada